



Masport[®]



100 YEARS
in the making
EST. 1910



Proudly designed and engineered in
New Zealand and sold all around the world.

THE MASPORT ADVANTAGE

Briggs & Stratton Ready Start™



Fitted to all lawnmowers powered by Briggs & Stratton 190cc engines.

Chipperchute



Allows your mower to shred branches up to 1 3/8" in diameter and turn them into mulch. As branches are chipped they are fed back into the catcher so you can put the mulch on your compost or garden.




Self Propelled




Let the mower do the work. These models are fitted with a self drive system, all you need to do is squeeze the handle.



Durable steel gears & pinions for long life.



Gearbox with controlled progressive cone clutch - smooth engagement, so you don't tear up the lawn.



Pinions & Pawls to act as a differential, allowing cornering without ripping or tearing up the lawn.

Wash Port



Hose fitting point on the housing to clean the aluminium housing while the mower engine is running, increasing the life of the deck and improving cutting efficiency.



Combo

Combination of Catch and Mulch options on these mowers.

Adjustable Dual Bearing Wheels



Masport's dual ball bearing wheels include a threaded axle and nut for ease of adjustment.

Dual Mowzone



With the blade coverage extending beyond the wheel width on both sides, the mower can cut closer to walls, kerbs and fences, giving a cleaner finish to your lawn.



Four Blade Disc System



4 blade disc cutting system with swingback blades for superior cutting and catching performance, and crankshaft protection.



Bar Blade with Chipper Blade

Masport's one piece bar blade with additional chipper blade.



These blade systems are interchangeable

Ergo Adjustable Camlocks



Multiple handle height adjustment to combat back strain. Easy fold down for storage.



Zone Start

The conveniently positioned starter cord eliminates the need to bend all the way down to pull start, reducing the risk of back strain.



Mow without the catcher, and avoid the messy grass clumps. The Smartchute™ will side discharge clippings in a 'sidethrow' action as you mow.



Cut Heights

Masport walk behind lawnmowers come with single point one touch height adjusters. Our self propelled lawnmowers' cut height is 1" to 4".

Mulch & Catch



Naturally recycle the grass by recutting it and feeding it back into your lawn.



Handle Lift System

Handle lift on some models makes for easy catcher access and storage.

MASPORT LAWNMOWERS



WIDECUT 800ST SP 3'N 1

Steel: Self Propelled

- Powered by Briggs & Stratton 190cc Series 675 Ready Start™ engine
- 21" heavy duty steel chassis
- Front 8" & Rear 9" adjustable dual bearing wheels
- Comfortable upturned upper handle with soft grip
- Reinforced lower handle for added strength
- Ergo camlocks for adjustable handle position & fold down
- **Cut, Catch, Mulch & Side Discharge**
- Smartchute™ for side discharge
- Zone start for comfortable starting position
- Bar blade cutting system
- Aero Catcher - 2 bushel capacity
- Self propelled (Ground speed 3 mph)
- Single point cut height selector 1" to 4"



WIDECUT MSV 800AL SPV GENIUS 4'N 1

Alloy: Self Propelled

- Powered by Briggs & Stratton 190cc Series 675 Ready Start™ engine
- 21" heavy duty aluminium chassis
- Front 8" & Rear 9" adjustable dual bearing wheels
- MSV Ergonomic adjustable handle with soft grip
- Handle Lift system
- **Cut, Catch, Mulch, Side Discharge & Chip**
- Chipperchute & chipper blade
- Washport for ease of cleaning
- Smartchute™ for side discharge
- Zone start for comfortable starting position
- Bar blade grass cutting system
- Aero Catcher - 2 bushel capacity
- Variable Speed Self Propelled (Ground speed 2 mph - 4 mph)
- Single point cut height selector 1" to 4"

OTHER PRODUCTS IN OUR RANGE



Home Gardener

Accessories available:
Garden aerator, lawn edger and cleaning brush.



Cylinder Mower



Striper

Masport Limited
P O Box 14-349, Panmure
Auckland 1741, New Zealand
email: sales@masport.co.nz
web: www.masport.com



Manufactured by Masport, distributed by:

